

Features:

- No UV or IR light radiation.
- Provide 118° beam angles.
- Using high luminous efficiency LED, a single white module's luminous flux can be up to 14lm, luminous efficiency 46lm/w
- UV Stabilized plastic Lens and plastic Lamp Shell
- Life expectancy: 3 years \geq 13000 hours (L_{70}).
- All-inclusive aluminum process ensures good heat dissipation and high IP grade
- Correlated Color Temperature: 5500-6500K
- Operating temperature: -20°C ~ +60°C.
- DC12V
- Convenient to install: The standard cascade number 50 pcs modules. Two modules make a unit, no cut between each two modules.
- Other colors are available.

Application:

- Channel letters backlighting
- Indoor lighting and decoration
- Architecture lighting
- Advertising light box backlighting
- Sign board backlighting
- Commercial sign backlighting



Benefits

- Energy Cost Savings:
Over 80% Compared to Incandescent.
- Solid-State:
High-Shock & High-Vibration Resistant,
Both Electrical and Mechanical
- Eco-Friendly:
No Mercury, No Lead Content
- No Hazardous Emissions:
No UV or IR Radiation
- Constant Light Output:
Even Lighting, Non-Halation
- No glare, no stroboscopic
- Fine heat output structure

Product Specifications:

Lamp Shell	Plastic
Voltage	DC12 V
Wattage	0.3W/pcs
Color	White
IP	IP65
Operating Temperature	-20°C ~ +60°C
Storage Temperature	-30°C ~ +70°C
Net Weight per piece (g)	77.5g
Warranty period	24 month
Size	30MM×7MM×4.7MM
Standard connection	50 pcs
Conforming standard	CE\ROHS

Tips:

- Tolerable range for luminous flux,color rendering and rated power: ± 10%.
- Tolerable range for operating voltage: ± 5%.
- Testing temperature: 25 ± 1 °C.
- Warranty limited: 3 years or 13000 hours; Whichever comes first.
- The maximum cascade number is 50 pcs when supply power at one end. Do not exceed.

Product Selection Guide:

Product	Beam Angle	Total Lumens	CCT	Luminous Efficiency	CRI
LS-3528W2R	118°	14 ± 5%	5500-6500K	46lm/W	PF ≥ 75

LS-3528W2R


① ② ③ ④ ⑤

- ① LS: led Modules
- ② 3528: 3528 LED
- ③ W: W (white)
- ④ 2: 2 pcs of led per module
- ⑤ R: DC12V

Product Dimensions:

Product size: 30*7*4.7


Unit: mm



NOTES:

1. All dimensions unit in mm
2. Tolerances is $\pm 0.5\text{mm}$ unless otherwise noted.

Package Dimension



Installation Instructions and Warnings:

- Carton size:520*370*260mm:
- Each string has 50PCS,6 strings in one bag;
- Each inner bag has 14 small bags of modules (4200PCS),while each carton has 2 inner bags (8400 pcs);
- Net weight(NW): 13.44 (1±5%)Kg:
- Gross weight (GW):16.06 (1±5%)Kg: